

product According to whether the stain is water-, oil-, or grease-based, choose the appropriate product as follows:

water-based (water soluble) stains: Regulat

water- and oil-based stains: Relift

grease- and oil-based stains: Respot

unknown stains: Respot followed by Regulat

Attention Regulat and Relift are not recommended for use on delicate fabrics e.g. silk moiré.

Check carefully that the treated fabric is colourfast before carrying out stain removal. Spray a light mist of the appropriate stain removal product onto a white towel and rub gently on an inconspicuous area of the fabric. If the fabric bleeds colour, stop working and call the Fiber Seal Hot Line.

If the fabric proves colourfast, start the stain removal process by blotting or dabbing the stain with a clean towel moistened with the stain removal product. Moisten a fresh piece of the towel and blot once more. Repeat the procedure until no further soiling is transferred to the towel and the stain is almost dry.

After the application of Relift or Regulat, blot the treated area with a towel or sponge moistened with water.

No access should be permitted to the area until the treated area is completely dry.

5

6

FIBER-SEAL® (Otschweiz) AG  
Rietwiesenstrasse 18  
CH - 8593 KESSWIL

INSTRUCTION MANUAL  
SYSTEM-KIT



FIBER-SEAL®

<b>General Information / Contents of The System-Kit</b>	2
<b>Maintenance</b>	
General	
Regular Maintenance of Carpets	
Regular Maintenance of Soft Furnishings	3
<b>Stain Removal</b>	
General	4
Physical Removal	4
Chemical Removal / Product Selection	4

## General Information / Contents of The System-Kit

The System-Kit should be stored as near as possible to the treated items, in a cool area and away from direct sunlight.

The instruction manual should be kept in the Kit. Your Fiber Seal System-Kit contains:

1 bottle of Relift	1 special sponge
1 bottle of Regulat	1 white towel
1 aerosol Respot	1 instruction manual

The stain removal products will be replaced or replenished as necessary at each Quarterly Service, free of charge.

Attention is drawn to the safety procedures that should be followed when using the products. Fiber Seal are not responsible for damage caused through improper use of the System-Kit.

## Maintenance

### General

Soil in the form of dust, dirt particles, and grease accumulates daily on all carpets and fabrics. In order to extend the life of the treated fabric and to maintain a lasting, well-groomed appearance, Fiber Seal recommends the following procedures:

### Regular Maintenance of Carpets

Regular, systematic vacuuming of Fiber Seal treated carpets will help to remove surface and loosely-attached soiling.

Frequency of the vacuuming is determined by the level of soiling that accumulates in the room over a fixed period of time. Traffic areas require vacuuming on a daily basis in order to prevent a flattening of the carpet pile.

2

## Regular Maintenance of Soft Furnishings

As in the case of carpets, soft furnishings should also be vacuumed on a regular basis. In addition, accumulated fatty or greasy soil can be removed as follows:

Moisten a white cotton towel with **Regulat** (in the case of water-sensitive fabrics such as silk moiré or cotton velvet **Respot** is recommended). Wipe carefully the soiled fabric. Repeat the procedure until no more soil is transferred onto the towel. Replace or wash the soiled towel as necessary.

The advantage of this regular maintenance procedure lies in the fact that not only dust particles but also oil and fatty soils such as skin cream and newspaper print can be removed. A layer of fatty soil, for example, can accumulate on headboards as a result of regular contact with human hair and appears as a greasy stain on the fabric. Regular damp dusting helps to prevent the occurrence of such greasy stains.

## Stain Removal

### General

Stains should be removed as soon as possible after their occurrence.

Don't rub vigorously, as this might result in fibre damage.

Use only Fiber Seal System-Kit products on Fiber Seal treated carpets and fabrics.

Apply each stain removal product first onto a clean white towel and then onto the stain. Do not apply the product directly onto the stain.

If it is not possible to remove the stain, call the Fiber Seal Hot Line.

3

## Physical Removal

**fresh water-based spills** Fresh stains should be absorbed using the special sponge. Start at the edge of the stain and work inwards. Hold the sponge above the stain and, applying only light pressure, wait until the sponge becomes almost saturated. If necessary, repeat the procedure using a fresh piece of the sponge. Take care not to rub the stain or to press the stain into the fabric.

**dried water-based spills** Old, dried-in water-based stains should be blotted with a sponge or towel moistened in warm water. This method is not recommended on water-sensitive fabrics such as moiré.

**solid stains** Carefully lift any residue with the help of a blunt knife or spatula. Velvet fabrics or velvet-pile carpets should be brushed in the direction of the pile. Vacuum up any loosened residue.

**combination stains** Treat the solid and liquid parts of the stain using the methods described above.

## Chemical Removal / Product Selection

**Regulat** is a mild, pH neutral stain removal agent suitable for the removal of beverage stains.

**Relift** is an alkali, water-based solvent stain removal agent suitable for the removal of food and other protein-based stains.

**Respot** is a mild solvent-based agent suitable for removal of oil- and grease-based stains.

4